YLF sp. z o.o.
Rondo Daszyńskiego 2B
00-843 Warszawa, Poland (EU)
VAT: PL 554-29-33-015
+48 222 992 995
direct@airsup.eu

Dane aktualne na dzień: 28-03-2024 20:22

Link do produktu: https://airsup.eu/antenna-ci-292-3-fm2-meter-extended-band-frequency-138-174-mhz-p-31759.html



Antenna CI 292-3 FM/2 Meter Extended Band Frequency 138-174 MHz

Numer katalogowy	**21671059**
Kod producenta	**CI 292-3**
Kod EAN/Wewnętrzny	**5900004984106**

Opis produktu

Designed to provide 2.5:1 VSWR or better over a bandwidth of 138 to 174 MHz. Features a high-strength die-cast 3-hole aluminum base. Radiating element is a bent-whip tapered stainless steel rod suitable for bottom mounting. The CI 292-3 has been re-tested and upgraded to the new RTCA DO-160D environmental requirements.

SPECIFICATIONS

Electrical	
Frequency	138 to 174 MHz
VSWR	2.5:1 maximum
Polarization	Vertical
Radiation Pattern	Omnidirectional
Impedance	50 OHMS
Power	50 Watts
Mechanical	
Weight	0.5 lbs. maximum
Height	9.50 " maximum
Material	Die cast housing/stainless whip
Finish	Polyurethane enamel
Connector	BNC (female)
Environmental	
Temperature	-55 ° C to +70 ° C
Altitude	50,000 '
Air Speed	250 Knots TAS @ 25,000 '
Federal Specifications	
RTCA Environmental	DO-160D
Environmental Category	[D2X] ACB [R (C, C1) U (F, F1)] XWFDXSXXXXX [XX] X [XXXX] XAX
TSO FAA	C37d, C38d
RTCA MOPS	DO-186A
Connector	
BNC	Standard
Color	
White	Standard
Gasket	
Gasket	B29205