

Link do produktu: <https://airsup.eu/curtis-drain-valve-cca-1250-p-33221.html>

CURTIS DRAIN VALVE CCA-1250

Cena brutto	94,26 zł
Cena netto	76,63 zł
Numer katalogowy	21672537
Kod producenta	CCA-1250
Kod EAN/Wewnętrzny	5900020014108

Opis produktu

Quick opening brass drain valve for aircraft oil or fuel systems. A slight twist opens valve. No safety wire needed in closed position. FAA approved. TSO-C76 Approved.

Note: FAA Approval applies to fuel applications only. NOT FAA Approved for oil applications.

Curtis Superior Valve is experienced in valve design and can help solve your valve problems. In most cases a standard Curtis Superior Valve will do the job. Or possibly a slight modification of a production unit will answer a specific problem. We will be glad to give you any assistance you may require with your Quick Drain Valve application.

MAINTENANCE / CMM

Curtis Superior Valves are designed for installation in a standard NPT port for NPT threaded valves or an AND-10050 style port for UNF threaded valves. Use a sealant on NPT threaded valves or a fuel resistant o-ring of the proper size for UNF threaded valves. Refer to aircraft manufacturers torque specifications for the aircraft in which it is being used. Curtis Superior Valves require no special maintenance. Keep them reasonably clean and replace according to the prescribed synthetic rubber maintenance schedule for the aircraft in which they are used or 10 year usable life per Curtis Superior Valve whichever occurs first. Curtis Superior Valves cannot be OVERHAULED. Replace the entire valve per the maintenance schedule of the aircraft in which it is used or usable life per Curtis Superior Valve should it begin to leak.

OVERHAUL

Due to the low replacement cost of Curtis Quick Drain Valves versus the cost of replacement seals, breakage of seals in overhaul installations and labor costs, it is not recommended they be overhauled. Replace the entire valve in accordance with the instructions in MAINTENANCE above or should they begin to leak.

MATERIAL	A	Aluminum
	AA	Anodized Aluminum
	B	Brass
	BC	Brass Cadmium Plated
	SS	Stainless Steel

Use Curtis Fuel Sampling Cup P/N [CCA-39680 \(05-17300\)](#) for Fuel Testing

Field Replaceable O'Rings TSO C76 approval from the FAA

Valve Number	Valve Thread Spec.
CCA-1800	1/8 ANPT
CCA-1900	1/4 ANPT
CCA-2000	3/8-24 UNF-3A
CCA-2100	7/16-20 UNF-3A

FUEL VALVE & MANUFACTURERS CROSS REFERENCE

Curtis Part Number	Auto Valve Part Number	Saf-Air Part Number	Curtis Stem Seal O'Ring	Mounting O'Ring
CCA-1800	BJ1000AS1MY	CAV-110	MS29513-007	None Req.
CCA-1900	BJ1000AS1MX	CAV-160	MS29513-007	None Req.
CCA-2000	1100B52Z	CAV-180	MS29513-007	MS29513-011
CCA-2100	1100B52Z-G	CAV-170	MS29513-007	MS29513-012