



Garmin GSB 15

Cena brutto	1 647,71 zł
Cena netto	1 339,60 zł
Numer katalogowy	21678031
Kod producenta	010-02201-10

Opis produktu

Garmin GSB 15 Dual USB Charging Port (Type-A) - Install Version with vertikal connector, TSO-C71

Description

Add USB Power and Charging to Your Aircraft

Dual USB configuration gives simultaneous fast 3A charging from each port

Charge two full-size iPad® tablets or similar smart devices while using them at full brightness

Halo lighting around each USB port makes connections easy in dark conditions

Offers easy installation in an existing instrument cutout with optional adapter plate

Two charger formats — for straight or 90-degree power wiring connection — help simplify installation in tight spaces such as armrests or sidewalls

In just a few short years, battery-powered mobile devices have become essential in-flight tools for pilots and their passengers alike. Pilots use their tablets or smartphones to access flight plans, moving maps, charts, weather data, manuals and more — while passengers access entertainment, messaging and all types of productivity apps on their devices. But, invariably, all these portable electronics need an external power source to keep them charged and ready to use over a long flight. That's where our GSB 15 USB charging hub makes all the difference.

Power up on the Fly

This dual-port 3A USB charger delivers plenty of electrical current to power two iPad tablets or similar smart devices at full brightness — while simultaneously charging their batteries. There's built-in protection against circuit and temperature overloads. Plus, configurable halo lighting on the plugs makes them easy to locate and access in a darkened cabin or cockpit.

Small and Simple to Install

The slimline GSB 15 charging hub measures just over 1.5" square and stands less than an inch deep — making it one of the smallest dual-port USB charging hubs ever designed for aviation use. It comes in two formats: one designed to be wired into aircraft power from the back of the unit — and one that connects to aircraft power through the bottom of the case. Choose the version that fits best with your application and its related space constraints.

Fits Tight Spaces and Budgets

You can mount GSB 15 virtually anywhere. It's small enough to fit a 1" cutout — or it's available with two optional mounting plates that allow for easy installation in existing, unused 2.25" or 3.125" instrument holes in the panel. It has FAA TSO and consequently European approval. The device will fit in a variety of constricted spaces — such as aircraft sidewalls, armrests or aft console positions — where most aviation USB chargers are simply too large or unwieldy to install.

Specifications

Charging port type: USB Type-A

Input voltage: 14V, 28V

Output voltage: 5-12V

Power consumption:

Max (while charging): 40W

Min (not charging): 300mW

Maximum current output per port:

5V 3A

9V 2A

12V 1.5A

18W Max

Required circuit breaker size: 5A

Dimensions:

Right-angle Connector: 1.50" x 1.55" x 0.84"

Vertical Connector: 1.50" x 1.50" x 0.92"

Weight: 0.16 lbs

Certifications:

TSO-C71