

Link do produktu: <https://airsup.eu/hydraunycail-fh-6-aw-hydraulic-fluid-pail-20-lt-bms-3-32b-ty-1-cml-02cbb1-cml-d50022-p-41016.html>



HYDRAUNYCOIL FH 6 AW, HYDRAULIC FLUID, PAIL 20 LT // BMS 3-32B TY 1 & CML 02CBB1 & CML D50022

Cena brutto	2 555,81 zł
Cena netto	2 077,91 zł
Kod EAN/Wewnętrzny	2694101600009

Opis produktu

HYDRAUNYCOIL FH 6 AW
PETROLEUM-BASED SHOCK STRUT FLUID

BMS 3-32 C Type I
AIRBUS CML 02CBB1
BOEING CML D50022

Hydraunycail FH 6 AW is a rust-inhibited petroleum-based fluid with a viscosity of 15 cSt at 40°C. It contains a specific additive package to improve the fluid lubricity and extreme-pressure properties.

Applications :

- Shock strut fluid for landing gear absorber
- Helicopter systems
- Hydraulic fluid
- Landing gear fluid
- Leak testing
- Corrosion preventive
- Test bench
- Hydraulic actuators
- Missile hydraulic systems

Nota : Hydraunycail FH 6 AW is used as shock strut fluid for Airbus aircraft landing gears for both inflight operation and storage.