



## Mobile Jet 387 1 Qt

Cena brutto	<b>147,78 zł</b>
Cena netto	<b>120,15 zł</b>
Numer katalogowy	<b>21677947</b>
Kod producenta	<b>430280-00 1qt</b>
Kod EAN/Wewnętrzny	<b>5900074364105</b>

### Opis produktu

#### Description:

Mobil Jet Oil 387 has been developed to meet the performance requirements of both current and future, advanced gas turbine engines used in commercial and military service. Made from a specially prepared, ester base stock, Mobil Jet Oil 387 is fortified with a unique chemical additive package. The resulting lubricant has superior thermal and oxidation stability that resists deterioration and deposit formation. The physical properties of Mobil Jet Oil 387 conform to the required builder and military specifications.

#### Advantages:

Mobil Jet Oil 387 shows excellent performance controlling deposits typically experienced in both the liquid and vapor phases in bearing compartments, oil supply lines, and breather/scavenger lines. These properties have been confirmed in various laboratory tests, including the Corrosion-Oxidation Stability Test, Alcor Deposition Test, Vapor Phase Coker, Erdco High-Temperature Bearing Test, Ryder Gear, and the Mobil Thin Film Oxidation Test.

The closely controlled viscosity of Mobil Jet Oil 387 at -40°C (-40°F), and a pour point below -54°C (-65°F), ensure the good low-temperature fluidity which permits starting and lubrication at temperatures as low as -40°C. In extensive laboratory testing, Mobil Jet Oil 387 exhibits excellent bulk oil stability at temperatures greater than 225°C (437°F).

#### Applications:

Mobil Jet Oil 387 is approved against the new SAE AS5780 High-Performance Capability (HPC) standard. This civil specification was developed to meet the growing performance and quality needs that commercial airlines seek, especially with the entrance of new, higher-output, and lower consumption engines.

OEM in-house evaluation/approval programs are also underway. Once complete, Mobil Jet Oil 387 will be commercialized for use in aircraft gas turbine engines, including turbo-jet, turbo-fan, turbo-prop, and turbo-shaft (helicopter), in commercial and military service. In addition, it will be suitable for aircraft-type gas turbine engines in industrial and marine applications.

Mobil Jet Oil 387 is compatible with other synthetic gas turbine lubricants meeting U.S. Military Specification MIL-PRF-23699. Mixing with other products, however, could result in some loss of its superior performance features. The lubricant is completely compatible with all metals used in gas turbine construction, as well as with F Rubber (Viton A), H Rubber (Buna N), and other commonly used seal materials.

#### Engine/OEM Evaluations:

- Mobil Jet Oil 387 has the following builder approvals: \*
- General Electric Aviation
- Rolls Royce
- Pratt & Whitney
- Honeywell APUs
- UTC Aerospace Systems APUs, Generators and Starters
- Mobil Jet Oil 387 has the following builder approvals in progress : \*
- CFM International
- Engine Alliance
- International Aero Engines

- Honeywell turbine engines
- Mobil Jet Oil 387 has the following approvals:
- PRI-QPL-AS5780/HPC
- MIL-PRF-23699-HTS